

FIG. 1




FIG. 1

FIG. 1A




FIG. 1B




FIG. 1C

ARRIVING DEVICE
 SELECTS ATTRIBUTES OF
 INTEREST IN THE ACCESSED
 SERVICE RECORDS
 OR
 DETERMINES THE
 CHARACTERISTICS OF THE
 RECEIVED SIGNALS FROM
 THE MASTER DEVICES
 IN MULTIPLE PICONETS




FIG. 1D

ARRIVING DEVICE
FORMS A NETWORK DISCOVERY
MENU INCLUDING DESCRIPTIONS
OF AD HOC NETWORK
APPLICATION PROGRAMS
RUNNING IN MULTIPLE PICONETS,
DERIVED FROM THE ACCESSED
SERVICE RECORDS AND
RANKED ACCORDING TO THE
SELECTED ATTRIBUTES OR TO THE
SIGNAL CHARACTERISTICS







FIG. 1D

FIG. 1E



09891382-062701

FIG. 1F




FIG. 1G





FIG. 1G

FIG. 2A






FIG. 2B

FIG. 2C

ARRIVING
WIRELESS DEVICE 100

HYPERLINKS 235




FIG. 2C

FIG. 3

START HERE




FIG. 3A CREATE REGISTRY FOR NEW MEMBER OF PICONET PROGRAM 280




FIG. 3B

INITIAL MENU
APPLICATION
PROGRAM
300




FIG. 3C




FIG. 3D




FIG. 3E

SERVICE RECORD
UPDATE
(APPLIC. PGM)
330
↓

SERVICE RECORD UPDATE ROUTINE

SET VALUES FROM LOCAL AD HOC NETWORK APPLICATION PROGRAM

ServiceRecordHandle = HANDLE_UUID

ServiceClass = "NETWORK_SERVICE"

ProtocolDescriptorList = PROTOCOLS

AttributeIdentifier1 = ATTRIBUTE_ID_1

AttributeType1 = "STRING"

AttributeSize1 = SIZE

AttributeData1 = STRING_DATA

AttributeIdentifier2 = ATTRIBUTE_ID_2

AttributeType2 = "INTEGER"

AttributeSize2 = SIZE

AttributeData2 = PICONET_ACCESS_CODE

WRITE UPDATED SERVICE RECORD TO LOCAL SDP SERVICE REGISTRY AS

ServiceRecordHandle / ServiceClass / ProtocolDescriptorList /

AttributeIdentifier1 / AttributeType1 / AttributeSize1 / AttributeData1 /

AttributeIdentifier2 / AttributeType2 / AttributeSize2 / AttributeData2

RETURN

FIG. 3E

FIG. 3F

340

BEGIN NETWORK DISCOVERY MENU APPLICATION IN ARRIVING DEVICE

DISPLAY NETWORK DISCOVERY MENU

OPTION STRING

- | | |
|---|--|
| 1 | "BASEBALL CUBS VS. METS 3RD INNING SCORE 2 TO 2" |
| 2 | "CAD COLLABORATION NEED HELP DESIGNING BRIDGE TRUSS" |
| 3 | "INDIVIDUALS CONNECTED TO INTERNET GATEWAY DEVICE" |

WAIT FOR SELECTION

IF OPTION = 1 THEN

SEND PAGE TO AD HOC BASEBALL PICONET MASTER DEVICE
 USING AD HOC BASEBALL PICONET_ACCESS_CODE

RECEIVE ID PACKET FROM AD HOC BASEBALL MASTER DEVICE
 WHICH ASSUMES TEMPORARY ROLE AS REMOTE SLAVE
 TO ARRIVING DEVICE WHICH ASSUMES TEMPORARY ROLE AS
 MASTER IN A TEMPORARY NEW PICONET

SET UP LINK BETWEEN ARRIVING DEVICE AND REMOTE DEVICE
REQUEST BY ARRIVING DEVICE TO SWITCH MASTER/SLAVE ROLES
ARRIVING DEVICE BECOMES SLAVE AND REMOTE DEVICE RESUMES
 MASTER ROLE IN AD HOC BASEBALL PICONET

ELSE IF OPTION = 2 THEN

SEND PAGE TO AD HOC COLLABORATION PICONET MASTER DEVICE
 USING AD HOC COLLABORATION PICONET_ACCESS_CODE

RECEIVE ID PACKET FROM AD HOC COLLABORATION MASTER
SET UP LINK BETWEEN ARRIVING DEVICE AND REMOTE DEVICE
REQUEST BY ARRIVING DEVICE TO SWITCH MASTER/SLAVE ROLES
ARRIVING DEVICE BECOMES SLAVE AND REMOTE DEVICE RESUMES
 MASTER ROLE IN AD HOC COLLABORATION PICONET

ELSE IF OPTION = 3 THEN

SEND PAGE TO AD HOC INTERNET GATEWAY PICONET MASTER DEVICE
 USING AD HOC INTERNET GATEWAY PICONET_ACCESS_CODE

RECEIVE ID PACKET FROM AD HOC INTERNET GATEWAY MASTER
SET UP LINK BETWEEN ARRIVING DEVICE AND REMOTE DEVICE
REQUEST BY ARRIVING DEVICE TO SWITCH MASTER/SLAVE ROLES
ARRIVING DEVICE BECOMES SLAVE AND REMOTE DEVICE RESUMES
 MASTER ROLE IN AD HOC INTERNET GATEWAY PICONET

ELSE RETURN

FIG. 3F

FIG. 3G

**NETWORK
COLLABORATION
(APPLIC. PGM)**
350

BEGIN CAD NETWORK COLLABORATION
IF LOCAL DEVICE IS PICONET MASTER
THEN GO TO BROADCAST ROUTINE
ELSE GO TO UPDATE SCORE ROUTINE

352

MASTER BROADCAST ROUTINE

IF NEW DATA HAS BEEN RECEIVED FROM A SLAVE DEVICE
THEN FORWARD NEW DATA TO AD HOC NETWORK INFO PROVIDER
ELSE IF NEW DATA HAS BEEN GENERATED BY MASTER DEVICE
THEN SEND NEW DATA TO AD HOC NETWORK INFO PROVIDER
ELSE GO TO UPDATE ROUTINE

354

UPDATE CAD DESIGN ROUTINE

UPDATE DESIGN STATUS WITH NEW DATA
SET VALUES FOR HANDLE_UUID, PROTOCOLS
SET VALUES FOR ATTRIBUTE_ID_1, SIZE
SET STRING STRING_DATA =
"CAD COLLABORATION" + "NEED HELP DESIGNING" +
NEED1+ NEED2+ NEED3
SET VALUES FOR ATTRIBUTE_ID_2, SIZE,
SET INTEGER PICONET_ACCESS_CODE = MASTER BD_ADDR
CALL SERVICE RECORD UPDATE ROUTINE (FIG. 3E)
TO CREATE UPDATED SERVICE RECORD
IF LOCAL DEVICE IS NOT AD HOC NETWORK INFO PROVIDER ,
THEN SEND UPDATED SERVICE RECORD TO MASTER DEVICE
FOR FORWARDING TO AD HOC NETWORK INFO PROVIDER
GO TO CAD NETWORK COLLABORATION ROUTINE

356

CAD NETWORK COLLABORATION ROUTINE

CORE CAD NETWORK COLLABORATION PROGRAM GENERATES NEW DATA
CALL SERVICE RECORD UPDATE ROUTINE (FIG. 3E)
TO CREATE UPDATED SERVICE RECORD
IF LOCAL DEVICE IS NOT AD HOC NETWORK INFO PROVIDER ,
THEN SEND UPDATED SERVICE RECORD TO MASTER DEVICE
FOR FORWARDING TO AD HOC NETWORK INFO PROVIDER
RETURN

358

FIG. 3G

FIG. 4A BLUETOOTH PACKET STRUCTURE
FOR AN INQUIRY PACKET
SENT BY ARRIVING DEVICE 100



FIG. 4B BLUETOOTH FHS PACKET STRUCTURE
FOR AN INQUIRY RESPONSE PACKET
SENT BY AD HOC NETWORK
INFORMATION PROVIDER 106




FIG. 4C

BLUETOOTH PACKET STRUCTURE
FOR A PAGING PACKET
SENT BY ARRIVING DEVICE 100




FIG. 4D

BLUETOOTH PACKET STRUCTURE
FOR A PAGE ACKNOWLEDGEMENT PACKET
SENT BY AD HOC NETWORK INFORMATION
PROVIDER 106




FIG. 4E
BLUETOOTH PACKET STRUCTURE FOR
SDP SERVICE SEARCH ATTRIBUTE REQUEST PACKET
SENT BY ARRIVING DEVICE 100
TO AD HOC NETWORK INFORMATION PROVIDER 106






FIG. 4F

BLUETOOTH PACKET STRUCTURE FOR RESPONSE TO
SDP SERVICE SEARCH ATTRIBUTE REQUEST,
RESPONSE SENT BY AD HOC NETWORK INFORMATION PROVIDER 106
TO ARRIVING DEVICE 100



BLUETOOTH PACKET STRUCTURE FOR
SDP SERVICE SEARCH ATTRIBUTE REQUEST PACKET
SENT BY ARRIVING DEVICE 100
TO AD HOC NETWORK INFORMATION PROVIDER 106



BLUETOOTH PACKET STRUCTURE FOR RESPONSE TO
SDP SERVICE SEARCH ATTRIBUTE REQUEST,
RESPONSE SENT BY AD HOC NETWORK INFORMATION PROVIDER 106
TO ARRIVING DEVICE 100





FIG. 41

BLUETOOTH PACKET STRUCTURE FOR
SDP SERVICE SEARCH ATTRIBUTE REQUEST PACKET
SENT BY ARRIVING DEVICE 100
TO AD HOC NETWORK INFORMATION PROVIDER 116



BLUETOOTH PACKET STRUCTURE FOR RESPONSE TO
SDP SERVICE SEARCH ATTRIBUTE REQUEST,
RESPONSE SENT BY AD HOC NETWORK INFORMATION PROVIDER 116
TO ARRIVING DEVICE 100




FIG. 4K

BLUETOOTH PACKET STRUCTURE FOR
SDP SERVICE SEARCH ATTRIBUTE REQUEST PACKET
SENT BY ARRIVING DEVICE 100
TO AD HOC NETWORK INFORMATION PROVIDER 126




FIG. 4L

BLUETOOTH PACKET STRUCTURE FOR RESPONSE TO
SDP SERVICE SEARCH ATTRIBUTE REQUEST,
RESPONSE SENT BY AD HOC NETWORK INFORMATION PROVIDER 126
TO ARRIVING DEVICE 100




FIG. 5




FIG. 5A

FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A

FIG. 6A




FIG. 6B






FIG. 7



IEEE 802.11 PACKET STRUCTURE FOR PROBE REQUEST,
SENT BY ARRIVING DEVICE 100(I) TO
AD HOC NETWORK INFORMATION PROVIDER 106(I)



IEEE 802.11 PACKET STRUCTURE FOR PROBE RESPONSE TO PROBE REQUEST,
THIS RESPONSE SENT BY AD HOC NETWORK INFORMATION PROVIDER 106(I)
TO ARRIVING DEVICE 100(I)




FIG. 7C

FIG. 7C




FIG. 8

ARRIVING DEVICE 100(H2)
 FORMS A NETWORK
 DISCOVERY MENU OF THE
 SUBNETS DERIVED FROM
 THE SERVICE RECORDS
 ACCESSED FROM THE
 AD HOC NETWORK
 INFORMATION PROVIDERS
 106(H2), 116(H2), 126 (H2)




FIG. 8A

HIPERLAN TYPE 2 MAC FRAME STRUCTURE 800
INCLUDING RANDOM CHANNEL RESOURCE REQUEST 836,
SENT BY ARRIVING DEVICE 100(H2) TO
CENTRAL CONTROLLER DEVICE 104(H2)





FIG. 8B

HIPERLAN TYPE 2 MAC FRAME STRUCTURE 800'
INCLUDING SERVICE RECORD REQUEST 838,
SENT BY ARRIVING DEVICE 100(H2) TO
AD HOC NETWORK INFORMATION PROVIDER 106(H2)



HIPERLAN TYPE 2 MAC FRAME STRUCTURE 800"
INCLUDING SERVICE RECORD RESPONSE 848,
SENT BY AD HOC NETWORK INFORMATION PROVIDER 106(H2)
TO ARRIVING DEVICE 100(H2)




FIG. 8D

